



POINT BREAK CLEANER TDS 240

PURPOSE

Table with 2 columns: Product Name (Powerful Organic Spot Cleaner) and Description (Dislodges and cleans common non-greasy stains)

ADVANCED ORGANIC STAIN REMOVER

FEATURES

Table with 2 columns: Feature (e.g., Damage Free, Spot Cleaning) and Description (e.g., Efficiently cleans moss, mold, mildew, leaf stains)

SUITABLE SURFACES

- Concrete & Clay Pavers, Natural & Manufactured Stone, Travertine, Flat Concrete, Segmental Retaining Wall Blocks, Concrete Walls, Exposed Aggregate, Not for use on asphalt

*Use caution on sensitive surfaces such as wet cast pavers and stamped concrete. May cause damage to color of surface.

PERFORM A TEST IN A SMALL AREA TO VERIFY SUITABILITY, DILUTION RATE AND DWELL TIME OF THIS PRODUCT FOR YOUR STAIN.

COVERAGE PER GALLON OF DILUTED PRODUCT

Table with 3 columns: APPLICATION, SQ FEET, SQ METERS

Coverage based on single treatment. Some applications may require additional treatments. Coverage rate may vary depending on the surface porosity, texture, severity of staining, application method and other local conditions.

SURFACE PREPARATION/PRE-TESTING

- Remove all loose soil and debris from surface. Cover/protect adjacent and surrounding surfaces not intended to be cleaned. TEST FIRST: Before using Point Break, test on a small, inconspicuous area to determine the suitability, correct dilution and dwell time needed for your surface.

DILUTION INSTRUCTIONS

Dilute with water prior to use. Amount of dilution is dependent on severity of staining and if surface has been previously sealed. Only use strength of dilution needed to sufficiently clean. Under dilution (too strong) may cause damage to the substrate.

- Pour desired amount (see chart) of Point Break into an empty, clean 1 quart or 1 gallon container.
- Fill the balance of the container with water and mix.

DILUTION CHART

Dilution Ratio (Water : Point Break)	Point Break for 1 ready to use quart	Point Break for 1 ready to use gallon	Strength/Application
3:1	8 oz.	32 oz.	Maximum for difficult stains
15:1	2 oz.	8 oz.	Moderate for common stains
30:1	1 oz.	4 oz.	Minimum for light stains and cleaning on sealed surfaces

APPLICATION CONDITIONS

- Clean when air and surface temperatures are 40°F or above. If freezing conditions exist, allow time for surface to thaw.
- If air temperature exceeds 90°F, flash cool the surface with water before applying product.
- Do not allow product to dry on a hot surface.
- Always rinse thoroughly while cleaner is still wet on surface.

APPLICATION TOOLS

- Low pressure sprayer such as a pump-up garden sprayer or spray bottle
- Clean stiff bristle brush or broom
- Hot water pressure washer preferred. As an alternative, cold water pressure washer or garden hose can be used.

APPLICATION INSTRUCTIONS

Point Break is designed for one application cleaning. Stronger concentrations and additional cleanings may be needed to remove heavier, deep set stains.

- Apply dilution of Point Break using a low pressure sprayer.
- Let dwell for 5 to 10 minutes.
- Improve results by scrubbing surface with a brush to agitate and break down stains.
- For brushless cleaning, apply Point Break on the surface using two applications back to back. The first application is to penetrate and the second is to lift the stain out.
- Rinse surface thoroughly. For best results, use a hot water pressure washer with a 25° to 40° fan tip to draw out and further break down surface stains. A cold water pressure washer or a garden hose with nozzle may be used as a substitute. Only use as much pressure needed to thoroughly clean as excessive high pressures can damage substrates.
- Let surface dry. Inspect stains to determine if additional spot cleaning is needed.
- Clean the entire surface with Trident's Wipe Out or White Water surface cleaners following manufacturer's instructions.
- Before installing joint sand or sealing, allow surface to dry.

CLEAN UP

Rinse all tools and overspray thoroughly with water before product dries.

STORAGE

- Store locked up in a cool, well-ventilated place
- Do not allow to freeze

PACKAGING

1 Gallon Containers - 4 Per Case 55 Gallon Drums
5 Gallon Pails

DISPOSAL

Dispose of contents and container to appropriate waste site or reclaimer in accordance with all applicable laws, regulations, and product characteristics at time of disposal.

SHELF LIFE

2 years when unopened and properly stored

PRECAUTIONARY INFORMATION

- **KEEP OUT OF REACH OF CHILDREN**
- Read label before use
- Use only outdoors in a well ventilated area
- Keep container tightly closed when not in use
- Avoid breathing vapors, spray or mist
- Do not get in eyes, on skin or on clothing
- Wash thoroughly after handling
- Do not eat, drink or smoke when using this product
- Wear protective gloves, clothing, face and eye protection
- Avoid release to the environment

EMERGENCY & FIRST AID MEASURES

- Get medical attention if exposed and you feel unwell, or are concerned.
- **IF INHALED:** Remove victim to fresh air and keep at rest in a position comfortable for breathing.
- **IF SWALLOWED:** Rinse mouth. Do NOT induce vomiting. Call a POISON CENTER or physician if feel unwell.
- **IF ON SKIN (or hair):** Take off all contaminated clothing and wash before reuse. Wash with plenty of water or shower. If skin irritation occurs: Get medical advice/attention.
- **IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation occurs: Get medical attention.
- **IN CASE OF FIRE:** Use water, water fog, dry chemical, CO₂ or alcohol resistant foam to extinguish.

See Safety Data Sheet for complete information.

WARRANTY

Trident warrants its products to substantially conform to its published specifications at the time of purchase. The foregoing is the sole limited warranty applicable to the products. Trident HEREBY DISCLAIMS ALL OTHER WARRANTIES OF ANY KIND OR NATURE, WHETHER EXPRESS, IMPLIED, OR STATUTORY, INCLUDING WITHOUT LIMITATION THE IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR ANY OTHER WARRANTY OTHER THAN THE WARRANTY SET FORTH ABOVE. The user is solely responsible for determining suitability of the products for their particular use. While the actual application of this product is out of the control of Trident, it is recommended that the application guidelines be followed completely and accurately. Trident's liability for any damage shall not exceed the purchase price of the product used, and it shall have no liability for consequential, incidental or punitive damages.

