

Point Break | Page 1 | TDS 240 | Revised Date: 11.20.25

PURPOSE

Advanced Organic Stain Remove	•	Dislodges and cleans common non-greasy stains
-------------------------------	---	---

ADVANCED ORGANIC STAIN REMOVER

FEATURES

	Efficiently cleans moss, mold, mildew, leaf stains		
Damage Free, Spot Cleaning	 Tough on rust, wine and non-greasy food stains 		
	 Does not damage or etch surfaces with proper dilution 		
Flexi-Dilute	Customize strength of dilution to match stains		
Fast Acting	Attacks stains in minutes		
Clean Rinse Technology	Easily rinse away dirt and cleaner residue with a low or high pressure washer		
Biodegradable	Cleaner residue breaks down quickly in soil		
Concentrated Formula	Dilute to meet cleaning needs		

SUITABLE SURFACES

- Concrete & Clay Pavers
- Natural & Manufactured Stone
- Travertine
- Flat Concrete

- Segmental Retaining Wall Blocks
- Concrete Walls
- Exposed Aggregate
- Not for use on asphalt

*Use caution on sensitive surfaces such as wet cast pavers and stamped concrete. May cause damage to color of surface.

PERFORM A TEST IN A SMALL AREA TO VERIFY SUITABILITY, DILUTION RATE AND DWELL TIME OF THIS PRODUCT FOR YOUR STAIN.

COVERAGE PER GALLON OF DILUTED PRODUCT

APPLICATION	SQ FEET	SQ METERS
All Surfaces	100 - 250	9.3 - 23.2

Coverage based on single treatment. Some applications may require additional treatments. Coverage rate may vary depending on the surface porosity, texture, severity of staining, application method and other local conditions.

SURFACE PREPARATION/PRE-TESTING

- Remove all loose soil and debris from surface.
- Cover/protect adjacent and surrounding surfaces not intended to be cleaned.
- **TEST FIRST:** Before using Point Break, test on a small, inconspicuous area to determine the suitability, correct dilution and dwell time needed for your surface. Allow test area to dry thoroughly before evaluating final appearance and results.

Point Break | Page 2 | TDS 240 | Revised Date: 11.20.25

DILUTION INSTRUCTIONS

Dilute with water prior to use. Amount of dilution is dependent on severity of staining and if surface has been previously sealed. Only use strength of dilution needed to sufficiently clean. Under dilution (too strong) may cause damage to the substrate.

- Pour desired amount (see chart) of Point Break into an empty, clean 1 quart or 1 gallon container.
- Fill the balance of the container with water and mix.

DILUTION CHART

Dilution Ratio (Water : Point Break)	Point Break for 1 ready to use quart	Point Break for 1 ready to use gallon	Strength/Application
3:1	8 oz.	32 oz.	Maximum for difficult stains
15:1	2 oz.	8 oz.	Moderate for common stains
30:1	1 oz.	4 oz.	Minimum for light stains and cleaning on sealed surfaces

APPLICATION CONDITIONS

- Clean when air and surface temperatures are 40°F or above. If freezing conditions exist, allow time for surface to thaw.
- If air temperature exceeds 90°F, flash cool the surface with water before applying product.
- Do not allow product to dry on a hot surface.
- Always rinse thoroughly while cleaner is still wet on surface.

APPLICATION TOOLS

- Low pressure sprayer such as a pump-up garden sprayer or spray bottle
- Clean stiff bristle brush or broom
- Cold or hot water pressure washer preferred with 25° to 40° tip or garden hose with nozzle

APPLICATION INSTRUCTIONS

Point Break is designed for one application cleaning. Stronger concentrations and additional cleanings may be needed to remove heavier, deep set stains.

- Apply dilution of Point Break using a low pressure sprayer.
- Let dwell for 5 to 10 minutes.
- Improve results by scrubbing surface with a brush to agitate and break down stains.
- For brushless cleaning, apply Point Break on the surface using two applications back to back. The first application is to penetrate and the second is to lift the stain out.
- Rinse surface thoroughly. For best results, use a hot water pressure washer with a 25° to 40° fan tip to draw out and further break down surface stains. A cold water pressure washer or a garden hose with nozzle may be used as a substitute. Only use as much pressure needed to thoroughly clean as excessive high pressures can damage substrates.
- Let surface dry. Inspect stains to determine if additional spot cleaning is needed.
- Clean the entire surface with Trident's Wipe Out or White Water surface cleaners following manufacturer's instructions.
- Before installing joint sand or sealing, allow surface to dry.

Point Break | Page 3 | TDS 240 | Revised Date: 11.20.25

CLEAN UP

Rinse all tools and overspray thoroughly with water before product dries.

STORAGE

- Store locked up in a cool, well-ventilated place
- Keep container tightly closed.
- Do not allow to freeze

PACKAGING

1 Gallon Containers - 4 Per Case

5 Gallon Pails

DISPOSAL

Dispose of contents and container to appropriate waste site or reclaimer in accordance with all applicable laws, regulations, and product characteristics at time of disposal.

SHELF LIFE

2 years when unopened and properly stored

PRECAUTIONARY INFORMATION

- KEEP OUT OF REACH OF CHILDREN
- Use only outdoors or in a well ventilated area
- Keep away from heat/sparks/open flames/hot surfaces
- Keep only in original container
- Avoid breathing dust/fume/gas/mist/vapors/spray
- Do not eat, drink or smoke when using this product
- Wear protective gloves/ protective clothing/ eye protection/ face protection
- Wash skin thoroughly after handling

EMERGENCY & FIRST AID MEASURES

- Call a POISON CENTER or doctor/physician if you feel unwell. Absorb spillage to prevent material damage.
- IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. Call a POISON CENTER or doctor/physician if you feel unwell.
- IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing and wash it before reuse. Wash with plenty of soap and water. If skin irritation occurs: Get medical attention/advice.
- IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
- **IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists. Get medical advice/attention.
- IN CASE OF FIRE: Use any means suitable for extinguishing surrounding fire.

See Safety Data Sheet for complete information.

WARRANTY

Trident warrants its products to substantially conform to its published specifications at the time of purchase. The foregoing is the sole limited warranty applicable to the products. Trident HEREBY DISCLAIMS ALL OTHER WARRANTIES OF ANY KIND OR NATURE, WHETHER EXPRESS, IMPLIED, OR STATUTORY, INCLUDING WITHOUT LIMITATION THE IMPLIED WARRANTIES OF MERCHANT-ABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR ANY OTHER WARRANTY OTHER THAN THE WARRANTY SET FORTH ABOVE. The user is solely responsible for determining suitability of the products for their particular use. While the actual application of this product is out of the control of Trident, it is recommended that the application guidelines be followed completely and accurately. Trident's liability for any damage shall not exceed the purchase price of the product used, and it shall have no liability for consequential, incidental or punitive damages.

