

**PURPOSE**

Sea Wall | Page 1 | TDS 144 | Revised Date: 12.5.2023

<b>Water Repelling, Salt Blocking Surface Protection</b>	<ul style="list-style-type: none"> <li>Protects surface from water, salt &amp; freeze/thaw damage</li> </ul>
--	--

**ULTRA WATER REPELLING & SALT BLOCKING SEALER**

**FEATURES**

<b>Advanced Reactive Chemistry &amp; EZ Nano Technology</b>	<ul style="list-style-type: none"> <li>Provides ultimate surface protection against water and salt infiltration</li> <li>Prevents surface spalling caused by freeze/thaw environments</li> </ul>
<b>Superior Water Repellency</b>	<ul style="list-style-type: none"> <li>Inhibits biological growth such as mold, moss &amp; algae</li> </ul>
<b>High Performance Silane/Siloxane Blend</b>	<ul style="list-style-type: none"> <li>Does not contain any silicone or wax components</li> </ul>
<b>Breathable Immediate Application</b>	<ul style="list-style-type: none"> <li>Will not trap naturally occurring efflorescence and/or moisture</li> <li>Can be applied on a new, clean and dry surface without waiting* (see Surface Preparation)</li> </ul>
<b>Easy To Apply</b>	<ul style="list-style-type: none"> <li>Applies easily on dry or damp surfaces</li> <li>Apply two coats wet-on-wet for optimal performance</li> </ul>
<b>Invisible Penetrating Solvent Based Sealer</b>	<ul style="list-style-type: none"> <li>Does not alter the appearance of the surface (some surfaces may darken slightly)</li> <li>Non-film forming</li> <li>Consistency of water and clear in appearance when applied. Dries transparent.</li> </ul>
<b>Temperature Stable</b>	<ul style="list-style-type: none"> <li>Cured sealer is freeze resistant to -60°F (-51°C) and is stable up to 180°F (82°C).</li> </ul>

**IDEAL APPLICATIONS**

- Driveways
- Walk Ways/Stairs
- Garage Floors
- Industrial Flooring
- Building Entrances
- Shopping Malls
- Restaurant Drive-Thru
- Dumpster Pads
- Any high use hardscape surface where protection from water and salt are important.

**SUITABLE SURFACES**

- Concrete & Clay Pavers
- Natural & Manufactured Stone containing quartz or other silicas **MUST TEST FIRST\***
- Flat and Stamped Concrete
- Segmental Retaining Wall Blocks
- Concrete Walls
- Exposed Aggregate
- Unglazed Tile
- Grout
- Not recommended for marble, granite, ceramic tile and polished, honed or high gloss surfaces as they do not have enough surface texture to absorb the sealer. Do not use on asphalt.
- Performance may vary on limestone. Test first to verify performance and appearance before applying.

**PERFORM A TEST IN A SMALL AREA TO VERIFY PERFORMANCE AND APPEARANCE BEFORE APPLYING.**

**\*Due to the variability and physical make-up of natural stone this step is required to verify desired performance and appearance.**

**COVERAGE PER GALLON**

APPLICATION	SQ FEET	SQ METERS
Pavers & Other Hardscape Surfaces	75 - 200	6.9 - 18.6
Concrete	100 - 200	9.3 - 18.6
Retaining Walls & Other Vertical Surfaces	50 - 200	4.6 - 18.6

Coverage based on two coats applied wet-on-wet at right angles to first coat. Use approximately two thirds of the estimated amount on the first coat and one third on the second ensuring saturation. Actual coverage may vary depending on the type, age, condition, joint size and porosity of the surface, application method and other local conditions such as temperature.

## SURFACE PREPARATION

- **Test First:** Test first on a small inconspicuous area to determine suitability and if desired results are achievable with this product on your specific surface. Sea Wall may slightly darken some surfaces.
- **New Concrete, Mortar, Grout or Overlays:** Sea Wall should be applied once concrete is fully cured (30 days after installation) to ensure optimal performance.
- **Clean Surface:** Surface should be thoroughly cleaned with Trident's cleaners and free from curing compounds, oil, dust, loose material, and previously applied sealer other than Trident's Sea Wall sealer. Thoroughly rinse all cleaner residue prior to sealing.
- If installing **joint sand/polymeric sand**, install prior to sealing with Sea Wall. Activate polymeric sand per manufacturer's instructions.
- **Allow surface to dry for a minimum of 2 hours** after cleaning, polymeric sand activation and/or rain before sealer application. For optimal performance, a drier surface promotes better sealer penetration.
- Prior to sealing, **use a leaf blower to remove dust, debris and fine sand particles** from the surface prior to sealing.
- **Cover/Protect** nearby landscape, vehicles and buildings from overspray during application. **AVOID SEALER COMING IN CONTACT WITH GLASS.**

## APPLICATION CONDITIONS

- Apply when day and night temperatures are between 40°F - 95°F.
- Surface can be damp with no ponding or pooling of water present. For optimal performance, a drier surface promotes better sealer penetration.
- Avoid windy conditions to keep sealer spray from drifting.
- NO pre-blending or mixing required. **DO NOT DILUTE.**

## APPLICATION TOOLS

- Low pressure, high volume sprayer. Sprayer should be of solvent resistant design with neoprene or Viton type fittings.
- Slit foam, solvent resistant roller

## APPLICATION INSTRUCTIONS

Sea Wall is designed for a two-coat application. Second coat must be applied immediately after the first coat (wet-on-wet).

### Spray & Back Roll Application:

- To apply sealer, hold sprayer nozzle perpendicular to the surface and overlap each spray pass. Make sure surface is completely saturated.
- At a right angle to the first application, apply the second coat "wet on wet", approximately 10 minutes after the first coat. Do not allow surface to dry between coats.
- **Immediately after second coat**, back roll with a foam roller to eliminate any pooling and to even out sealer.
- **Avoid contact with glass.** If this product is allowed to dry on glass a residue may be created that is not removable. If accidentally splashed on glass, flush immediately with mineral spirits or other solvent.

## DRY TIME

- Surface will be dry to the touch in 30 minutes assuming 65 - 85°F. Low surface or air temperature will extend dry times.
- Protect the surface from dust, rain, condensation, and traffic while drying.
- Area can be open to foot & vehicular traffic in 2 - 4 hours depending on site conditions.

## CLEAN UP

For tools and equipment, use mineral spirits or naphtha before product is allowed to dry.

## MAINTENANCE

Sealed surfaces should be properly maintained to get the best long-term performance from both the pavement and the Sea Wall sealer.

- Keep surface clear of buildup of dirt, grime and stains by rinsing with cold, clean water.
- If staining of surface does occur, Trident Sealers are compatible with Trident's Cleaners which can be used to remove general dirtiness, organic and inorganic stains like oils, food and beverages and mineral deposits from the surface.
- Test cleaners in inconspicuous area prior to cleaning.
- Be sure to check dilution rates for all cleaners to determine if they are ready to use or to determine appropriate dilution rate especially for sealed surfaces.
- Efflorescence should be removed using Trident's White Water efflorescence cleaner and a pressure washer, in conjunction with agitation from a natural fiber brush. Care should be taken to ensure that excessive pressure is not utilized, as it may erode joint sand and could damage the surface itself.
- Thoroughly rinse all cleaner off the surface before sealing.

## RE-APPLICATION

Re-application may need to be carried out every 5 - 10 years depending on the type of surface and environmental/site conditions.

## PACKAGING

5 Gallon Pails  
55 Gallon Drums

## SHELF LIFE

2 years when unopened and properly stored

## STORAGE

- Store locked up in original packaging and in a cool, well-ventilated place
- Sea Wall is a flammable liquid and should be stored away from heat, hot surfaces, sparks open flames and other ignition sources.
- Do not allow to freeze

## VOC CONTENT

< 600 g/L

## PRECAUTIONARY INFORMATION

- **KEEP OUT OF REACH OF CHILDREN**
- Do not eat, drink or smoke when using this product
- Use only outdoors in a well ventilated area
- Do not breathe vapors, spray or mist
- Keep away from heat, hot surfaces, sparks, open flames and other ignition sources
- Ground and bond container and receiving equipment
- Use explosion-proof equipment and only non-sparking tools
- Take action to prevent static discharge
- Wear protective gloves, clothing, face and eye protection
- Wash thoroughly after handling
- Avoid release to the environment

## EMERGENCY & FIRST AID MEASURES

- Get medical attention if exposed and you feel unwell.
- **IF INHALED:** Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or physician if feel unwell.
- **IF SWALLOWED:** Immediately call a POISON CENTER or physician. Do NOT induce vomiting.
- **IF ON SKIN:** Immediately take off all contaminated clothing and wash before reuse. Rinse skin with plenty of water or shower. Get medical attention if irritation occurs.
- **IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation occurs.
- **IN CASE OF FIRE:** Use CO<sub>2</sub>, dry chemical or alcohol resistant foam to extinguish.

**See Safety Data Sheet for complete information.**

## LIMITATIONS

Protect sealer from freezing and store in a cool place when not in use. In winter, keep in heated area. This sealer is not recommended for marble, granite, ceramic tile, polished, honed or high gloss surfaces as they do not absorb the sealer. A test area is ALWAYS recommended to determine product suitability and compatibility with your specific surface before use and to verify if desired results are achievable. Due to the inherent variability of natural stone and clay products, long term performance may vary. Please consult with Trident prior to sealing if there are concerns. Do not use below grade or where water is always present. Never try to seal wet surfaces with pooling or ponding of water. A minimum temperature of 40° (5°C) must be maintained for a period of 24 hours prior to application. Air temperature should not exceed 95°F (35°C) during application. Work should cease in inclement weather (rain or strong wind).

## WARRANTY

Trident warrants its products to substantially conform to its published specifications at the time of purchase. The foregoing is the sole limited warranty applicable to the products. Trident HEREBY DISCLAIMS ALL OTHER WARRANTIES OF ANY KIND OR NATURE, WHETHER EXPRESS, IMPLIED, OR STATUTORY, INCLUDING WITHOUT LIMITATION THE IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR ANY OTHER WARRANTY OTHER THAN THE WARRANTY SET FORTH ABOVE. The user is solely responsible for determining suitability of the products for their particular use. While the actual application of this product is out of the control of Trident, it is recommended that the application guidelines be followed completely and accurately. Trident's liability for any damage shall not exceed the purchase price of the product used, and it shall have no liability for consequential, incidental or punitive damages.

