# **WIPE OUT**

**CLEANER** 

**TDS 210** 

# **PURPOSE**

Wipe Out | Page 1 | TDS 210 | Revised Date: 11.20.25

Robust Surface Cleaner	Restores and deep cleans concrete, pavers, natural and manufactured stone
	<ul> <li>Prepares surface for sealing by creating optimal conditions for sealer adhesion and ultimate aesthetic value</li> </ul>

#### **ROBUST SURFACE CLEANER**

#### **FEATURES**

Damage Free, Concentrated Cleaning Chemistry	<ul> <li>Eliminates deep-set dirt, grime, tire scuffing and environmental soiling</li> <li>Does not damage or etch most surfaces with proper dilution*</li> <li>Super concentrated: One gallon of concentrated Wipe Out cleans 6500 SF at the standard dilution rate</li> </ul>	
Clean Rinse Technology	Easily rinse away dirt and cleaner residue with a low or high pressure washer	
Flexi-Dilute	Customize strength to match cleaning needs	
Environmentally Friendly, Biodegradable Formula	<ul> <li>Non-acid &amp; phosphate free</li> <li>Replaces harsh acid-based cleaners</li> <li>Helps neutralize acid based detergents and cleaners</li> </ul>	

#### SUITABLE SURFACES

- Concrete & Clay Pavers
- Natural & Manufactured Stone
- Travertine
- Flat Concrete

- Segmental Retaining Wall Blocks
- Concrete Walls
- Clay Roof Tiles

- Exposed Aggregate
- \*Use caution on sensitive surfaces such as wet cast pavers and stamped concrete. May cause damage to color of surface.

PERFORM A TEST IN A SMALL AREA TO VERIFY SUITABILITY, DILUTION RATE AND DWELL TIME BEFORE CLEANING ENTIRE SURFACE.

# COVERAGE PER GALLON OF DILUTED PRODUCT

APPLICATION	SQ FEET	SQ METERS
All Surfaces	100 - 250	9.3 - 23.2

Coverage based on single treatment. Some applications may require additional treatments. Coverage rate may vary depending on the surface porosity, texture, severity of staining, application method and other local conditions.

# **SURFACE PREPARATION/PRE-TESTING**

- Remove all loose soil and debris from surface.
- Cover/protect adjacent and surrounding surfaces not intended to be cleaned.
- **Inspect area** for visible staining to determine stain types and quantity. If necessary, perform spot cleaning with cleaners designed to attack the specific stains.
- **TEST FIRST:** Before using Wipe Out, test on a small, inconspicuous area to determine the suitability, correct dilution and dwell time needed for your surface. Allow test area to dry thoroughly before evaluating final appearance and results.

Wipe Out | Page 2 | TDS 210 | Revised Date: 11.20.25

#### **DILUTION INSTRUCTIONS**

Dilute with water prior to use. Amount of dilution is dependent on severity of staining and if surface has been previously sealed. Only use strength of dilution needed to sufficiently clean. Under dilution (too strong) may cause damage to the substrate.

- Pour desired amount of Wipe Out (see chart) into an empty, clean 1 or 5 gallon container.
- Fill the balance of the container with water and mix

# **DILUTION CHART**

<b>Dilution Ratio</b> (Water : Wipe Out)	Wipe Out Needed for 1 ready to use gallon	Wipe Out Needed for 5 ready to use gallons	Strength/Application
20:1	6 oz.	30 oz.	Maximum for difficult cleaning
35:1	3.5 oz.	18 oz.	Standard for general purpose cleaning
50:1	2.5 oz.	12 oz.	Minimum for light soil & cleaning on sealed surfaces

# APPLICATION CONDITIONS

- Clean when air and surface temperatures are 40°F or above. If freezing conditions exist, allow time for surface to thaw.
- If air temperatures exceed 90°F, flash cool the surface with water before applying product.
- Do not allow product to dry on a hot surface.
- · Always rinse thoroughly while cleaner is still wet on surface.

# **APPLICATION TOOLS**

- Low pressure, high volume sprayer
- Clean stiff bristle brush or broom
- Cold or Hot Water Pressure Washer, flat Surface Cleaner (optional)\_

# APPLICATION INSTRUCTIONS

Wipe Out is designed for one application cleaning. Stronger concentrations and additional cleanings may be needed to remove heavier, deep set stains.

- Apply dilution of Wipe Out using a low-pressure sprayer.
- Let dwell on surface for 5 to 10 minutes.
- Improve results by scrubbing surface with a brush to agitate and break down stains.
- For brushless cleaning, apply Wipe Out on surface using two applications back to back.
- Rinse surface thoroughly with a pressure washer with a 25° to 40° fan tip, flat surface cleaner attachment or a garden hose with nozzle. Only use as much pressure needed to thoroughly clean as excessive high pressures can damage substrates.
- Before installing joint sand or sealing, allow surface to dry.

#### **CLEAN UP**

Rinse all tools and overspray thoroughly with water before product dries.

#### **PACKAGING**

1 Gallon Containers - 4 Per Case 5 Gallon Pails 55 Gallon Drums Bulk Packaging Available

Wipe Out | Page 3 | TDS 210 | Revised Date: 11.20.25

# **STORAGE**

- Store separately and locked up
- Keep in a cool, well-ventilated place
- Do not allow to freeze.

#### **DISPOSAL**

Dispose of contents and container to appropriate waste site or reclaimer in accordance with all applicable laws, regulations, and product characteristics at time of disposal.

# **SHELF LIFE**

2 years when unopened and properly stored

# PRECAUTIONARY INFORMATION

- KEEP OUT OF REACH OF CHILDREN
- · Read label before use
- · Keep only in original container
- · Use only outdoors in a well ventilated area

- Do not get in eyes, on skin or on clothing
- · Wash skin thoroughly after handling
- Wear protective gloves, clothing, face and eye protection
- Avoid release to the environment

# **EMERGENCY & FIRST AID MEASURES**

- If medical advice is needed, have product container or label at hand. IF exposed, feel unwell or concerned: Get medical advice/ attention.
- IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
- IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. Immediately call a POISON CENTER or physician.
- IF ON SKIN (or hair): Take off all contaminated clothing and wash before reuse. Rinse skin with plenty of water/shower. Wash contaminated clothing before reuse. If skin irritation or rash occurs: Get medical advice/attention.
- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists, Get medical attention/advice.
- IN CASE OF FIRE: Use water spray, alcohol resistant foam, dry chemical, carbon dioxide or sand.

# See Safety Data Sheet for complete information.

# WARRANTY

Trident warrants its products to substantially conform to its published specifications at the time of purchase. The foregoing is the sole limited warranty applicable to the products. Trident HEREBY DISCLAIMS ALL OTHER WARRANTIES OF ANY KIND OR NATURE, WHETHER EXPRESS, IMPLIED, OR STATUTORY, INCLUDING WITHOUT LIMITATION THE IMPLIED WARRANTIES OF MERCHANT-ABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR ANY OTHER WARRANTY OTHER THAN THE WARRANTY SET FORTH ABOVE. The user is solely responsible for determining suitability of the products for their particular use. While the actual application of this product is out of the control of Trident, it is recommended that the application guidelines be followed completely and accurately. Trident's liability for any damage shall not exceed the purchase price of the product used, and it shall have no liability for consequential, incidental or punitive damages.

