



SAFE HARBOR CLEANER TDS 250

PURPOSE

Table with 2 columns: Product Name (Powerful Oil Spot Cleaner) and Description (Works on both petroleum and food based oil stains)

FAST ACTING OIL & GREASE SPOT REMOVER

FEATURES

Table with 2 columns: Feature Name (e.g., Damage Free, Spot Cleaning) and Description (e.g., Dissolves, encapsulates and removes petroleum and food based oil stains)

SUITABLE SURFACES

- Concrete & Clay Pavers, Natural & Manufactured Stone, Travertine, Flat Concrete, Segmental Retaining Wall Blocks, Concrete Walls, Exposed Aggregate, Not for use on asphalt. *Use caution on sensitive surfaces such as wet cast pavers and stamped concrete. May cause damage to color of surface.

PERFORM A TEST IN A SMALL AREA TO VERIFY SUITABILITY AND DWELL TIME OF THIS PRODUCT FOR YOUR STAIN.

COVERAGE PER GALLON

Table with 3 columns: APPLICATION, SQ FEET, SQ METERS. Row: All Surfaces, 100 - 240, 9.3 - 22.3

Coverage based on single treatment. Some applications may require additional treatments. Coverage rate may vary depending on the surface porosity, texture, severity of staining, application method and other local conditions.

SURFACE PREPARATION/PRE-TESTING

- Remove all loose soil and debris from surface. Cover/protect adjacent and surrounding surfaces not intended to be cleaned. TEST FIRST: Before using Safe Harbor, test on a small, inconspicuous area to determine the suitability, correct dilution and dwell time needed for your surface.

APPLICATION CONDITIONS

- Clean when air and surface temperatures are 40°F or above. If freezing conditions exist, allow time for surface to thaw.
- If air temperature exceeds 90°F, flash cool the surface with water before applying product.
- Do not allow product to dry on a hot surface.
- Always rinse thoroughly while cleaner is still wet on surface.

APPLICATION TOOLS

- Clean stiff bristle brush or broom
- Cold or hot water pressure washer with 25° to 40° tip or garden hose with nozzle

APPLICATION INSTRUCTIONS

Safe Harbor is designed for one application cleaning. Additional cleanings may be needed to remove heavier, deep set stains.

- Agitate Safe Harbor by stirring or shaking tightly covered container prior to use.
- Pour Safe Harbor undiluted (straight) on to the stain.
- Brush to completely cover stain.
- For hot and dry conditions, make a poultice with Safe Harbor using a white rag, white paper towels, white napkins (no dyes), unscented/non-colored kitty litter or saw dust. In a small container, add enough Safe Harbor and poultice material to adequately cover your stain. Soak the poultice material thoroughly so it is saturated, then apply to oil stain covering it completely.
- Allow cleaner or poultice to dwell on the surface for 30 minutes.
- Scrub stain with brush to agitate and further break down stain. Let Safe Harbor dwell on the surface an additional 30 minutes. Lightly re-apply Safe Harbor during dwell time if surface or poultice starts to dry out.
- Remove and discard poultice material, if used.
- Rinse surface thoroughly. For best results, use a hot water pressure washer with a 25° to 40° fan tip to draw out and further break down surface stains. Alternative tools for rinsing include a cold water pressure washer or a garden hose with nozzle. Only use as much pressure needed to thoroughly clean as excessive high pressures can damage substrates.
- Let surface dry. Inspect stains to determine if additional spot cleaning is needed. Secondary cleanings may be necessary with increased dwell times to remove aged, heavier, deep set oil stains.
- Clean the entire surface with Trident's Wipe Out or White Water surface cleaners following manufacturer's instructions.
- Before installing joint sand or sealing, allow surface to dry.

CLEAN UP

Rinse all tools and overspray thoroughly with water before product dries.

CONTAINER HANDLING/STORAGE

- Store locked up, in original packaging, in a cool, well-ventilated place
- Do not allow to freeze.

DISPOSAL

Dispose of contents and container to appropriate waste site or reclaimer in accordance with all applicable laws, regulations, and product characteristics at time of disposal.

SHELF LIFE

2 years when unopened and properly stored

PACKAGING

1 Gallon Containers—4 per case

5 Gallon Pails

55 Gallon Drums

PRECAUTIONARY INFORMATION

- **KEEP OUT OF REACH OF CHILDREN**
- Read label before use
- Use only outdoors in a well ventilated area
- Keep container tightly closed when not in use
- Avoid breathing vapors, spray or mist
- Do not get in eyes, on skin or on clothing
- Wash thoroughly after handling
- Do not eat, drink or smoke when using this product
- Wear protective gloves, clothing, face and eye protection
- Avoid release to the environment

EMERGENCY & FIRST AID MEASURES

- Get medical attention if exposed and you feel unwell, or are concerned.
- **IF INHALED:** Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical attention if irritation occurs.
- **IF SWALLOWED:** Rinse mouth. Do NOT induce vomiting. Call a POISON CENTER or physician if feel unwell.
- **IF ON SKIN (or hair):** Take off all contaminated clothing and wash before reuse. Wash with plenty of water or shower. Get medical attention if irritation occurs.
- **IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation occurs: Get medical attention.
- **IN CASE OF FIRE:** Use water, water fog, dry chemical, CO₂ or alcohol resistant foam to extinguish.

See Safety Data Sheet for complete information.

WARRANTY

Trident warrants its products to substantially conform to its published specifications at the time of purchase. The foregoing is the sole limited warranty applicable to the products. Trident HEREBY DISCLAIMS ALL OTHER WARRANTIES OF ANY KIND OR NATURE, WHETHER EXPRESS, IMPLIED, OR STATUTORY, INCLUDING WITHOUT LIMITATION THE IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR ANY OTHER WARRANTY OTHER THAN THE WARRANTY SET FORTH ABOVE. The user is solely responsible for determining suitability of the products for their particular use. While the actual application of this product is out of the control of Trident, it is recommended that the application guidelines be followed completely and accurately. Trident's liability for any damage shall not exceed the purchase price of the product used, and it shall have no liability for consequential, incidental or punitive damages.

